



PROVEN • DURABLE • RELIABLE • VERSATILE

Put It On & Go To Sleep



PTFE 100% Virgin Full Density Thread Sealant Tape



PTFE 100% Virgin Resin Thread Sealant Tape is a full density, heavy duty tape that permits quick, clean and economical sealing of threaded pipe connections of up to 2" (50.8mm). Its full density makes it ideal for applications requiring the best possible seal. The tape is 100% natural virgin PTFE with no added fillers or pigments. It is an all-purpose thread sealant tape.

Meets MIL-T-27730A, CID A-A-58092 (Oxygen Service) and FDA 21 CFR177.1550 specification.

PTFE Gas Line Thread Sealant Tape Physical Properties

Composition	100% Virgin PTFE
Colour Pigment or Filler	No
Density (Nominal)	1.2 – 1.4 g/cc
Thickness (Nominal)	0.0035" (0.89mm)
Maximum Pipe Size	2" (50.8mm)
Pressure Rating	Full vacuum to 10,000 psi
Temperature Range	-268°C to +287°C
pH Range	0 - 14
Applications	<ul style="list-style-type: none"> • Aggressive Chemicals • Gas Line • Oxygen • All Petroleum Oils and Fuels • Water • Steam • Air
Characteristics	<ul style="list-style-type: none"> • No age deterioration • Non-Toxic • Non-Absorbent • Non Flammable • Self-Lubrication • Unlimited Shelf Life
Certifications / Specifications	<ul style="list-style-type: none"> • MIL-T-27730A • CID A-A-58092 (Oxygen Service) • FDA 21 CFR177.1550
Country of Origin	USA
Width	1/4", 1/2", 3/4", 1", 2"

Everjoy Industrial Supplies Pte. Ltd.

38 Woodlands Industrial Park E1, #04-11 Singapore 757700

Telephone: + 65 6748 3093

Fax: +65 6748 7202

Email: admin@everjoy.com.sg