

Hand Pumps – Lever Series



JP-02 - 6002 0000

For acids, alkalis and water based chemicals

Pump material: Polypropylene
Shaft: Stainless steel 304
Seals: FKM
Flow rate: 0.3, 0.37 or 0.45 L/stroke depending on lever position
Pump tube length: 340 – 900 mm
Pump tube diameter: Maximum 40 mm
Thread adapter: G 1 ½" and G 2"
Weight: 0.84 Kg



JP-03 - 6003 0000

For oils, diesel, alcohol up to 50%, anti-freeze liquid, water, etc...

Pump material: Polypropylene
Shaft: Tool steel
Seals: NBR
Flow rate: 0.3, 0.37 or 0.45 L/stroke depending on lever position
Pump tube length: 340 – 900 mm
Pump tube diameter: Maximum 40 mm
Thread adapter: G 1 ½" and G 2"
Weight: 0.84 kg



JP-04 YELLOW - 6004 0000

FKM seal for acid

Pump material: Polypropylene
Shaft: Tool steel
Seals: FKM
Flow rate: 0.3 L/stroke
Pump tube length: 500 – 900 mm telescopic
Pump tube diameter: Max 34 mm
Thread adapter: G 2"



JP-04 BLUE - 6004 0001

NBR seal for mineral oil

Pump material: Polypropylene
Shaft: Tool steel
Seals: NBR
Flow rate: 0.3 L/stroke
Pump tube length: 500 – 900 mm telescopic
Pump tube diameter: Max 34 mm
Thread adapter: G 2"



JP-04 RED - 6004 0002

EPDM seal for alkaline

Pump material: Polypropylene
Shaft: Tool steel
Seals: EPDM
Flow rate: 0.3 L/stroke
Pump tube length: 500 – 900 mm telescopic
Pump tube diameter: Max 34 mm
Thread adapter: G 2"



JP-04 BLUE / WHITE – 6004 0003

Fluoropolymer seal for liquid food

Pump material: Polypropylene
Shaft: Tool steel
Seals: Fluoropolymer
Flow rate: 0.3 L/stroke
Pump tube length: 500 – 900 mm telescopic
Pump tube diameter: Max 34 mm
Thread adapter: G 2"



JP-09 - 6009 0000

Suitable for most highly liquid and slightly aggressive media such as acids, alkalis and chemicals. Better resistance than JP-02 due to its PP sheathed shaft.

Pump materials: Polypropylene
Seal: FKM
Flow rate: 0.5 litre/stroke
Telescopic suction tube: 3 parts, polyethylene
Suction depth: 960 mm
PE hose: 2 metres
Weight: 1.2 Kg

Thread G 2" for screwing for mounting on standard barrels.

Adapters available for plastic drums and cans of 60 – 200 litres.

Outlet piece DN19, ¾"

*The pump is not to be used for pumping hazardous media of classes A1 / AII and other flammable media or in an explosive environment.



JP-14 - 6014 0000

Suitable for thin fluid, non-flammable liquids such as diesel, machine oils, mineral oils etc.

Pump materials: Zinc alloy
Seals: NBR
Flow rate: 0.5 litre/stroke
Pump tube length: 450 - 840 mm
Pump tube diameter: 40 mm
Thread adapter: G 2"
Telescopic suction tube enables a universal use for all sizes of drum.



JP-15 - 6015 0000

Suitable for transferring most thin fluid, non-flammable media such as diesel, oils, anti-freeze liquid, etc.

Pump materials: Zinc plated steel
Seals: NBR
Flow rate: 0.35 litre/stroke
Pump tube length: 450 – 865 mm
Pump tube diameter: 40 mm

The telescopic suction tube enables a universal use for all barrel sizes.

G 1½" and G 2" drum adapter pump with discharge arc. The outlet has a ¾" thread, thus other connection options exist.