



**JP-08 - 6008 0000**

The pump is suitable for thin fluid, highly aggressive media such as acids and alkalis.

**Pump materials:** PVDF  
**Flow rate:** 0.3 litre/rotation  
**Pump tube length:** 3 cm x 35 cm

Hand pump is complete with discharge arc and drum adapter G 2".  
Regular lubrication required.



**JP-11 - 6011 0000**

Suitable for thin fluid, non-flammable liquids such as diesel, gear oil, heating oil, hydraulic oil, machine oil, mineral oil, motor oil etc. up to 1000 mPas.

**Pump materials:** Aluminum and zinc plated steel  
**Flow rate:** 1 litre/rotation, changing from forward to reverse transferring possible thus result to an optimal dosing.  
**Pump tube length:** 1080 mm  
**Pump tube diameter:** 53 mm  
**Head:** 15 metres  
**Horizontal distance:** 50 metres

Pump is complete with discharge hose and drum adapter G 2".



**JP-12 - 6012 0000**

Suitable for thin fluid, non-flammable liquids such as diesel, gear oil, heating oil, hydraulic oil, machine oil, mineral oil, motor oil etc.. up to 1,000mPas.

**Pump materials:** Aluminium and zinc plated steel  
**Seals:** NBR

**Flow rate:** 1 litre/rotation, changing from forward to reverse transferring possible, thus result to an optimal dosing

**Pump tube length:** 1080 mm  
**Pump tube diameter:** 53 (sieve) mm  
**Head:** 15 metres  
**Horizontal distance:** 50 metres

Pump is complete with special mineral oil hose 2000 mm, discharge arc and drum adapter G 2".



**JP-13 - 6013 0000**

Suitable for diesel, gear oil, heating oil, oils up to SAE 90, all other self-lubricating, non-aggressive and non-flammable media.

**Pump materials:** Cast iron housing  
**Seals:** NBR  
**Flow rate:** 0.25 litre/rotation

**Pump tube length:** 1000 mm, three parts therefore suitable for smaller containers and 200 litres drum  
**Pump tube diameter:** Maximum 40 mm  
**Head:** 15 metres  
**Horizontal distance:** 50 metres

Pump is complete with discharge arc and drum adapter G 2".