



Plastic & Anti-Static Hand Pumps



JP-05 - STAINLESS STEEL HAND PUMP

Suitable for flammable liquids such as solvents (including acetone) Certified: Risk analysis by TUEV Munich Order No.: 700 mm - 6005 0700 700 mm - Ex 6005 0700 1000 mm - 6005 1000 1000 mm - Ex 6005 10000 Suitable for flammable liquids.

 Pump materials:
 Stainless steel 316Ti

 Seal:
 PTFE

 Flow rate:
 0.3 – 0.6 litre/stroke

Pump tube length: 700 mm and 1000 mm Pump tube diameter: 32 mm Required accessories:

Discharge arc with PTFE seal and wing nut Hose connection made of %" or 1" stainless steel, with PTFE seal and nickel plated brass wing nut Drum adapter made of nickel plated brass R2" with fixing device

Anti-static set consisting of 4 copper cables (absolutely necessary when pumping flammable liquids)





JP-06 - 6006 0000 PLASTIC HAND PUMP

Suitable for water and slightly aggressive acids and alkalis.

Pump materials: Flow rate: Polyethylene and PVC 0.08litre/pumping process and 20 litres/at independent transferring 850 mm

Pump tube length:850 mmPump tube diameter:25 mm

Hand pump is complete with 130 cm long discharge hose and drum adapter G 2".

This hand pump is designed as a siphon pump. After the suction pipe and the discharge hose arc is filled manually the pump works independently.

