

PTFE Coated Fiberglass & High Modulus FilmTape







PTFE Coated Fiberglass tape with liner

PTFE Coated Fiberglass Tape – Self Wound

PTFE High Modulus Film Tape – Self Wound

Overview:

Our PTFE Coated Fiberglass tape are designed to last longer than similar products use as heat sealing tape. A2005E is an economy grade that perform up to 20% better than any popular brands, while A2005P is a our premium grade that perform up 35% longer than competitions. These tapes can be supplied with liner for die cutting or cut to size applications.

PTFE high modulus film tape is a premium grade that is unsurpassed by any similar competitive material and has an elongation of up to 300% at break. This material out-perform similar product used for downhole cable splicing.

| Part Number | HM426 | A2005E | A2005P | A2006 | A2007 | A2010 | A2012 |
|--|------------------------|------------------------|----------|----------|----------|-------|-------|
| Description | High Modulus PTFE Film | PTFE Coated Fiberglass | | | | | |
| Release Liner | No | No | Optional | Optional | Optional | Yes | Yes |
| Total Thickness (Nominal) (mm) | 0.08 | 0.127 | 0.130 | 0.150 | 0.180 | 0.254 | 0.305 |
| StandardWidth (mm) | | | | | | | |
| Roll Length (metre) | 10 | | | | | | |
| Core Size (mm) | 38 | | | | | 76.2 | |
| Dielectric Strength (kV) | 7 | 3.5 | 3.5 | 4.0 | 4.5 | 5.5 | 7.0 |
| Elongation (%) | 300 | < 5 | | | | | |
| Operating Temperature °C | -73 to +260 | | | | | | |
| Flame Retardant | Yes | | | | | | |
| *Application Note: Clean surface with IPA solvent when changing to a new tape each time to get the best result | | | | | | | |

Applications:















L Sealers





dmc sos

Vacuum Sealers

Telephone: + 65 6748 3093

Fax: +65 6748 7202

Email: admin@everjoy.com.sg