



DW 501 HVOF Spray Tape

Product Description:

DW 501 is a laminate of blue silicone rubber impregnated fiberglass fabric, a 4 mil (0.102mm) aluminium foil and fiberglass fabric designed for severe demanding performance including HVOF applications. The silicone adhesive will release cleanly from the surface after the high temperature process.

Application Information:

DW 501 is used as a masking tape for HVOF spraying. The double-ply construction provides superior protection in this demanding high velocity spraying process.

DW 501 Technical data			
Properties	Test Method	Values	
Material	Blue Silicone Impregnated Fiberglass, 4 mil (0.102mm) aluminium and fiberglass fabric		
Adhesive System	Silicone		
		Imperial	Metric
Backing Thickness		0.018"	0.0457cm
Adhesive Thickness		0.005"	0.013 cm
Adhesion Strength	ASTM D1000	55 oz./in.	613.86 g/cm
Continuous Operating Temperature		500°F	260°C
FAA Regulation	GE Standard Practices	Approved	
Rolls-Royce Aero Repair	OMAT 2/174G	Approved	
Packaging			
Core I.D.		3"	7.62cm
Width		0.25" to 36"	0.635 to 91.44 cm
Roll Length		36 yards	32.92 metres
<p>This technical data are of typical values and should not be used to write specifications, create warranties of any kind. Users should determine the suitability of the product for their applications.</p>			

For Technical Service Support and Supplies : Contact Our Key Asia Distributor and Converter

Everjoy Industrial Supplies Pte. Ltd.

38 Woodlands Industrial Park E1, #04-11 Singapore 757700

Tel.: +65 6748 3093

Fax: +65 6748 7202

Email: salesmgnt@everjoy.com.sg