

High quality PTFE coated and laminated fabrics are ideal release product to cover heat sealing plate in PVC window frame production.

We supply PTFE release fabrics in roll, fabricated sheets and sleeves.


Laminates A2106LRR, A2106LRR & 02108LRB are designed to provide longer service life cutting substantial cost from stoppage time for replacement.

Operation Guide


Temperature setting: 250°C ~ 260°C (Actual temperature: 230°C ~ 250°C)

Welding duration: 5 ~ 10 seconds

Material change period: 3 ~ 5 days



A2106LRR



02108RB

Item	Unit	02006	A2006	02106	A2106	02106LRR	A2106LRR	02108LRB
Colour	Visual	Natural	Natural	Natural	Natural	Red	Red	Red/Blue
Fabric type	Coating	Coating	Coating	Coating	Coating	Laminated	Laminated	Laminated
Adhesive	-	No	Silicone	No	Silicone	No	Silicone	No
Backing thickness	mm	0.14	0.14	0.15	0.15	0.17	0.17	0.20
Total thickness	mm	0.14	0.20	0.15	0.20	0.17	0.23	0.20
Weight (Backing)	g/m ²	296	296	316	316	340	340	400
PTFE content	%	63	63	65	65	69	69	73
Tensile strength	N/5 cm	1200	1200	1200	1200	1400	1400	1500
Operating Temperature	°C	-73 to +260						
Standard Width	mm	1000, 1525	1000, 1525	1000	1000	1000	1000	1000

For Technical Service Support and Supplies : Contact Exclusive Asia Distributor and Converter

Everjoy Industrial Supplies Pte. Ltd.

38 Woodlands Industrial Park E1, #04-11 Singapore 757700

Tel.: +65 6748 3093

Fax: +65 6748 7202

Email: salesmgnt@everjoy.com.sg